

## Specifications DEN<sup>+</sup>

Model	JV-DEN	JV-12DEN	JV-36DEN	JV-60DEN	JV-84DEN
Dimensions (W x D x H)	950 x 540 x 920 mm	950 x 540 x 1,345 mm	950 x 540 x 1,690 mm	950 x 540 x 1,850 mm	950 x 540 x 2,090 mm
Weight (Except canister)	About 135 kg	About 150 kg	About 175 kg	About 190 kg	About 205 kg
Canister capacity	-	12EA (L4: 12)	36EA (L1: 12, L2: 24)	60EA (S: 36, L: 12, L1: 12)	84EA (S: 60, L: 12, L1: 12)
Maximum working rate	Unit-dose: Max. 60pack/min, Multi-dose: Max. 50pack/min				
STS working rate	Max. 60pack/min				
STS capacity	60pack/1tray				
Auto Canister working rate	-	Max. 40 pack/min			
Auto Canister Capacity	-	Max. 500 tablet (Based on 1 Tablet sized 7 mm)			
Pouch sizes (W x H)	Selectable from 70 x 55 mm (Unit-dose only), 70 x 75 mm, 70 x 82 mm				
Tablet detection	Infrared light detection				
Power consumption	550W				
Power Supply	America: 120V~, 60Hz / Europe: 220-240V~, 50/60Hz				
Operation Temperature / Humidity	0~40°C / 10~80%				
Printing system	Thermal transfer system: any number of typefaces is possible (Cartridge Type)				
Text Info	Possible to support graphic Windows environment (Possible to print all characters and barcode)				
<b>Additional Option</b>	-	Auto Canister: Max. 4EA	Auto Canister: Max. 8EA		
	-	Automatic recognition of tablet location (ACRS)			
	Touch Screen 38 cm (15") + Holder				
	STS Tray Light				