

## Specifications DOC<sup>+</sup>

Model	JV-102DOC	JV-156DOC
Dimensions (W x D x H)	780 x 550 x 1,720 mm	780 x 550 x 1,970 mm
Weight (Except canister)	About 270 kg	About 300 kg
Canister capacity	102EA (S: 48, L: 27, L1: 27)	156EA (S: 102, L: 27, L1: 27)
Maximum working rate	Unit-dose: Max. 60pack/min, Multi-dose: Max. 50 pack/min	
STS working rate	Max. 60pack/min	
STS capacity	30 pack/1 tray	
Auto Canister working rate	Max. 40 pack/min	
Auto Canister Capacity	Max. 500 tablet (Based on 1 Tablet sized 7 mm)	
Pouch sizes (W x H)	Selectable from 70 x 55 mm (Unit-dose only), 70 x 75 mm, 70 x 82 mm	
Tablet detection	Infrared light detection	
Display and input	Touch Screen 25.6 cm (10.1") / All in one IPC	
Power consumption	550W	
Power Supply	America: 120V~, 60Hz / Europe: 220-240V~, 50/60Hz	
Operation Temperature / Humidity	0~40°C / 10~80%	
Printing system	Thermal transfer system: any number of typefaces is possible (Cartridge Type)	
Text Info	Possible to support graphic Windows environment (Possible to print all characters and barcode)	
Additional Option	Auto Canister: Max. 4EA	
	Automatic recognition of tablet location (ACRS)	
	STS Tray Light	
	Door opening direction (L type or R type)	