

## Specifications NS<sup>+</sup>

| Model                            | JV-300NS   | JV-360NS                          | JV-420NS                          | JV-480NS                          | JV-576NS                          |
|----------------------------------|--|-----------------------------------|-----------------------------------|-----------------------------------|-----------------------------------|
| Dimensions (W x D x H)           | 970 x 870 x 2,000 mm   | 970 x 870 x 2,180 mm              | 1,260 x 1,020 x 2,000 mm          | 1,260 x 1,020 x 2,000 mm          | 1,260 x 1,020 x 2,180 mm          |
| Weight (Except canister)         | About 650 kg   | About 700 kg                      | About 970 kg                      | About 985 kg                      | About 1,070 kg                    |
| Canister capacity                | 300EA<br>(S: 120, L: 120, L1: 60)  | 360EA<br>(S: 120, L: 180, L2: 60) | 420EA<br>(S: 168, L: 168, L1: 84) | 480EA<br>(S: 192, L: 192, L1: 96) | 576EA<br>(S: 192, L: 288, L2: 96) |
| Maximum working rate             | Unit-dose: Max. 65pack/min, Multi-dose: Max. 50pack/min  |                                   |                                   |                                   |                                   |
| STS working rate                 | Max. 55pack/min  |                                   |                                   |                                   |                                   |
| STS capacity                     | 60pack/1tray   |                                   |                                   |                                   |                                   |
| U-Canister working rate          | Max. 40 pack/min   |                                   |                                   |                                   |                                   |
| U-Canister Capacity              | Max. 280 tablet (Based on 1 Tablet sized 9.8 mm x 4.2 t)   |                                   |                                   |                                   |                                   |
| Pouch sizes (W x H)              | Selectable from 70 x 55 mm (Unit-dose only), 70 x 75 mm, 70 x 82 mm  |                                   |                                   |                                   |                                   |
| Tablet detection                 | Infrared light detection   |                                   |                                   |                                   |                                   |
| Display and input                | Touch Screen 25.6 cm (10.1") / All in one IPC  |                                   |                                   |                                   |                                   |
| Power consumption                | 800W   |                                   |                                   |                                   |                                   |
| Power Supply                     | America: 120V~, 60Hz / Europe: 220-240V~, 50/60Hz  |                                   |                                   |                                   |                                   |
| Operation Temperature / Humidity | 0~40°C / 10~80%  |                                   |                                   |                                   |                                   |
| Printing system                  | Thermal transfer system: any number of typefaces is possible (Cartridge Type)  |                                   |                                   |                                   |                                   |
| Text Info                        | Possible to support graphic Windows environment (Possible to print all characters and barcode)   |                                   |                                   |                                   |                                   |
|                                  | U-Canister: Max. 6EA   |                                   | Max. 7EA                          |                                   | Max. 8EA                          |
|                                  | Pouch sizes Changeable (70 x 56 mm/70 x 65 mm/70 x 75 mm/70 x 85 mm/70 x 95 mm)<br>* 70 x 50mm: Specific size is used as per SW option setting |                                   |                                   |                                   |                                   |
| Additional Option                | Automatic recognition of tablet location (ACRS)  |                                   |                                   |                                   |                                   |
|                                  | Slide rack Auto open Function  |                                   |                                   |                                   |                                   |
|                                  | STS Auto open Function   |                                   |                                   |                                   |                                   |
|                                  | Removable Main Frame   |                                   |                                   |                                   |                                   |

\* Product exterior and specifications are subject to change due to the company's research and development results without any prior notice.

\* Dispensing speed may vary by pouch size.