

Specifications NSP⁺

Model	JV-420NSP10	JV-480NSP10	JV-576NSP10
Dimensions (W x D x H)	1,260 x 1,020 x 2,070 mm	1,260 x 1,020 x 2,070 mm	1,260 x 1,020 x 2,250 mm
Weight	About 1,010 kg	About 1,025 kg	About 1,110 kg
Canister capacity	420EA (S: 168, L: 168, L1: 84)	480EA (S: 192, L: 192, L1: 96)	576EA (S: 192, L: 288, L2 96)
Maximum working rate	Max. 30pack/min		
STS capacity	60pack/1 tray		
U-Canister Capacity	Max. 280 tablet (Based on 1 Tablet sized 9.2 mm x 4.2 t)		
Pouch sizes (W x H)	Changeable (70 x 56mm/70 x 65mm/70 x 75mm/70 x 85mm/70 x 95mm) * 70 x 50 mm: Specific size is used as per SW option setting		
Tablet detection	Infrared light detection		
Display and input / PC	Touch Screen 25.6 cm (10.1") / All in one IPC / VISION IPC		
Camera	1296 x 966 (1.3M) 31 fps, 2CCD multi-spectral camera		
Main Frame	Swappable Main Frame		
Canister type	Automatic recognition of tablet location (ACRS)		
STS	STS Auto open Function, STS Tray Light		
Power consumption	800W		
Power Supply	America: 120V~, 60Hz / Europe: 220-240V~, 50/60Hz		
Operation Temperature / Humidity	0 ~ 40°C / 10 ~ 80%		
Printing system	Thermal transfer system: any number of typefaces is possible. Cartridge Type		
Text info	Possible to support graphic Windows environment. Possible to print all characters and barcode		
Additional Option	U-Canister: Max. 7EA	U-Canister: Max. 8EA	

* Product exterior and specifications are subject to change due to the company's research and development results without any prior notice.